



# Comfortstep B

Shin protection during ascent and descent and attractive design ensure high comfort when working and a flexible range of applications.

## Product description

- 80 mm deep treads with padded front edges.
- Abrasion-resistant, anodised stiles.
- High-strength perlon belts prevent splay.
- Treads with plastic-cushioned front edges.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.
- Screwed connection between treads and stile.



## Product features

Anti splay: Belt strap

Coating: anodised

Connection Stile-Rung: bolted

Load: max. 150 kg

Material: Aluminium

Pitch rung/tread: 250 mm

Producttype: Bolted stepladder with treads

Tread depth: 80 mm

Type rung/tread: padding on front tread edges



## Hints and special features

Maximum comfort due to padded treads.  
Complies with EN 131 Professional.

## Product variants

Order number	Base	Number of treads	Number of treads	Overall base width	Overall length	Stile depth	Transport dimensions	Vertical ladder height	Weight	Working height
41432	0,74 m × 0,44 m	3	2 × 3	0,44 m	0,84 m	42 mm	840 mm × 445 mm × 174 mm	0,75 m	4,4 kg	2,25 m
41433	0,95 m × 0,47 m	4	2 × 4	0,47 m	1,11 m	42 mm	1,110 mm × 470 mm × 174 mm	1 m	5,8 kg	2,5 m
41434	1,15 m × 0,5 m	5	2 × 5	0,5 m	1,38 m	42 mm	1,380 mm × 500 mm × 174 mm	1,25 m	7,3 kg	2,75 m
41435	1,35 m × 0,53 m	6	2 × 6	0,53 m	1,65 m	42 mm	1,650 mm × 530 mm × 174 mm	1,5 m	8,8 kg	3 m
41436	1,55 m × 0,56 m	7	2 × 7	0,56 m	1,92 m	42 mm	1,920 mm × 560 mm × 174 mm	1,75 m	10,3 kg	3,25 m
41437	1,75 m × 0,59 m	8	2 × 8	0,59 m	2,18 m	48 mm	2,185 mm × 590 mm × 174 mm	2 m	12,2 kg	3,5 m
41438	2,16 m × 0,65 m	10	2 × 10	0,65 m	2,72 m	48 mm	2,725 mm × 650 mm × 174 mm	2,5 m	15,8 kg	4 m
41430	2,36 m × 0,68 m	11	2 × 11	0,68 m	2,99 m	48 mm	3,000 mm × 680 mm × 174 mm	2,75 m	17,6 kg	4,25 m