

EFAmix S

The special ladders for all applications in electrical environments.

Product description

- Aluminium alloy treads, 80 mm deep, with non-slip serrated surface.
- Can be used for work on electrical installations, thanks to insulating stiles made from glass-fibre-reinforced plastic.
- Safety platform (250 x 250 mm).
- Safe storage of accessories and tools in an aluminium storage tray.
- Only 88 mm wide when folded.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478.
- Treads made from extruded aluminium section.



Product features

Connection Stile-Rung: flanged
 Load: max. 150 kg
 Material: Aluminium / plastic
 Pitch rung/tread: 230 mm
 Platform length: 250 mm
 Platform width: 250 mm
 Producttype: GRP composite stepladder with treads
 Stile depth: 50 mm
 Stile depth: 50 mm
 Stile depth steps/back stay: 50mm / 50mm
 Tray: Plastic
 Tread depth: 80 mm
 Type rung/tread: serrated

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions	Weight	Working height
40431	0,75 m × 0,52 m	3	0.52 m	1.4 m	0.68 m	1.390 mm × approx. 520 mm × 100 mm	6 kg	2.7 m
40432	0,91 m × 0,55 m	4	0.55 m	1.65 m	0.91 m	1.640 mm × approx. 550 mm × 100 mm	7 kg	2.9 m
40433	1,07 m × 0,57 m	5	0.57 m	1.9 m	1.14 m	1.890 mm × approx. 570 mm × 100 mm	8 kg	3.15 m



Order number	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions	Weight	Working height
40434	1,24 m × 0,6 m	6	0.6 m	2.15 m	1.37 m	2.140 mm × approx. 600 mm × 100 mm	9 kg	3.35 m
40435	1,4 m × 0,62 m	7	0.62 m	2.4 m	1.6 m	2.390 mm × approx. 620 mm × 100 mm	10 kg	3.6 m