PaxTower S-PLUS 1T

With advanced guardrail for extra safety and compliance with the new EN 1004:2020

Product description

- One-handed operation of the folding frame featuring a sturdy lock button: Engage or release the lock with simple click.
- Patented toeboard unit: Quick to install.
- Smooth-sliding guides made of hard plastic: Prevent misalignment when connecting push-on end frames together.
- Scaffolding length: 1.80 m; scaffolding width: 0.72 m.
- Safer and quicker assembly and dismantling due to advanced guardrails and platforms at intervals of 2 m.
- Scaffolding Category 3 (load capacity of up to 200 kg/m²) according to the new EN 1004.
- 125 mm swivel castors with brake; the castors can be fitted with castor adapters (order no. 42974) to allow for height adjustment.
- Stile and rung diameter 45 mm.

Product features

Claw type: automatic
Fits through doorways: Yes
Height-adjustable castors:: No
Platform length: 1.8 m
Platform length: 1.8 m
Platform size: 0,6m × 1,8m
Platform width: 0.6 m
Rung diameter: 45 mm
Scaffolding class: 3 (= 200 kg/m²)
Stile diameter: 45 mm
Wheel diameter: 125 mm
Width scaffolding: 0.72 m

Product variants

Order number	Overall height	Platform height	Transport dimensions	Weight	Working height
53521	1.65 m	0.55 m	1.950 mm × 750 mm × 400 mm	38.3 kg	2.55 m
53522	2.65 m	1.55 m	2.150 mm × 750 mm × 700 mm	71.4 kg	3.55 m
53523	3.65 m	2.55 m	2.150 mm × 750 mm × 750 mm	79.5 kg	4.55 m
53524	4.65 m	3.55 m	2.150 mm × 750 mm × 950 mm	108 kg	5.55 m
53525	5.65 m	4.55 m	2.150 mm × 750 mm × 1.100	114.1 kg	6.55 m

Order number	Overall height	Platform height	Transport dimensions	Weight	Working height
			mm		
53526	6.65 m	5.55 m	2.150 mm × 750 mm × 1.300 mm	142.6 kg	7.55 m