

Nova S

The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.

Product description

- 80 mm deep surfaces to stand on.
- Large platform with anti-slip ribbing.
- Practical tray with plenty of space for tools and small items.
- Strong Perlon rung hooks and rung locking mechanism, from 7 rungs.
- Patented tread construction: robust, stable, durable, flanged rung-stile connection.
- The extruded aluminium sections give the platform optimum stability.
- Two extruded section bridge raisers.
- Firm positioning thanks to anti-slip plastic end caps.
- Enclosed rung profile and integrated guide tube.



Product features

Coating: natural
 Connection Stile-Rung: flanged
 Load: max. 150 kg
 Material: Aluminium
 Pitch rung/tread: 216 mm
 Platform length: 250 mm
 Platform width: 250 mm
 Producttype: Stepladder with flanged treads
 Stile depth: 48 mm
 Stile depth: 48 mm
 Stile depth steps/back stay: 48mm / 48mm
 Tray: Plastic
 Tread depth: 80 mm
 Type rung/tread: serrated
 Warranty: 10 years

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Anti splay	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Transport dimensions
42453		0,69 m × 0,42 m	3	0,42 m	1,34 m	0,61 m	1.350 mm × 420 mm × 120 mm
42454		0,84 m × 0,44 m	4	0,44 m	1,57 m	0,83 m	1.580 mm × 440 mm × 120 mm
42455		0,99 m × 0,46 m	5	0,46 m	1,8 m	1,05 m	1.810 mm × 470 mm × 120 mm
42456		1,14 m × 0,49 m	6	0,49 m	2,03 m	1,26 m	2.060 mm × 490 mm × 120 mm
42457	Belt strap	1,28 m × 0,51 m	7	0,51 m	2,26 m	1,48 m	2.270 mm × 520 mm × 120 mm
42458	Belt strap	1,44 m × 0,54 m	8	0,54 m	2,49 m	1,7 m	2.500 mm × 540 mm × 120 mm