XLstep S

Low weight, simple handling and a good price/ performance ratio with high-value equipment.



Product description

- Treads with a depth of 80 mm for fatigue-free standing.
- Abrasion-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm × 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Spacious aluminium storage tray for material and tools.
- High-strength Perlon belts prevent splay, fitted on all models of 4 rungs or more.
- Triple-riveted connection between treads and stiles.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.

Product features

Coating: anodised
Connection Stile-Rung: riveted
Load: max. 150 kg
Material: Aluminium
Pitch rung/tread: 250 mm
Platform length: 250 mm
Platform width: 300 mm
Producttype: Riveted stepladder with treads
Stile depth: 42 mm
Tray: Aluminium
Tread depth: 80 mm
Type rung/tread: serrated
Warranty: 10 years

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Anti splay	Base	Number of rungs, incl. platform	Overall base width	Overall length	Platform height	Stile depth
41223		0,74 m × 0,49 m	3	0.49 m	1.56 m	0.74 m	42 mm
41224	Belt strap	0,91 m × 0,52 m	4	0.52 m	1.83 m	0.99 m	42 mm
41225	Belt strap	1,08 m × 0,55 m	5	0.55 m	2.1 m	1.24 m	42 mm
41226	Belt strap	1,25 m × 0,57 m	6	0.57 m	2.37 m	1.49 m	48 mm
41227	Belt strap	1,42 m × 0,61 m	7	0.61 m	2.64 m	1.74 m	48 mm
41228	Belt strap	1,59 m × 0,63 m	8	0.63 m	2.91 m	1.99 m	48 mm
41230	Belt strap	1,93 m × 0,69 m	10	0.69 m	3.45 m	2.49 m	48 mm