

Scana B

Flexible working and pleasant to handle due to the anodised stiles.

Product description

- Tread depth 80 mm.
- Wear-resistant, anodised stiles.
- High-strength Perlon straps prevent splay.

Product features

Anti-splay mechanism: Belt strap
 Coating: anodised
 Connection between stiles and rungs/stiles: riveted
 Load: max. 150 kg
 Material: aluminium
 Product type: Riveted stepladder with treads
 Stile depth: 40 mm
 Tread depth: 80 mm
 Type of rungs/treads: serrated
 Vertical distance between each rung/tread: 216 mm
 Warranty: 10 years



Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Base	Number of treads	Number of treads	Overall base width	Overall length	Transport dimensions	Vertical ladder height
44203	0,59 m × 0,43 m	3	2 × 3	0,43 m	0,71 m	710 mm × 430 mm × 160 mm	0,66 m
44204	0,76 m × 0,45 m	4	2 × 4	0,45 m	0,94 m	940 mm × 460 mm × 160 mm	0,87 m
44205	0,91 m × 0,48 m	5	2 × 5	0,48 m	1,17 m	1.170 mm × 480 mm × 160 mm	1,09 m
44206	1,1 m × 0,5 m	6	2 × 6	0,5 m	1,4 m	1.400 mm × 500 mm × 160 mm	1,3 m
44207	1,28 m × 0,52 m	7	2 × 7	0,52 m	1,66 m	1.630 mm × 530 mm × 160 mm	1,52 m